


Deep Impact Socket

3435S

3/8"

- ANSI / ASME B107.2




| KT NO. | inch | D1 mm | D2 mm | l mm | L mm | g | kg |
|---------|-------|-------|-------|------|------|-----|---------|
| 343508S | 1/4 | 10.8 | 19 | 10 | 63.5 | 62 | 6 / 120 |
| 343510S | 5/16 | 13.0 | 19 | 12 | 63.5 | 71 | 6 / 120 |
| 343512S | 3/8 | 15.3 | 19 | 12 | 63.5 | 82 | 6 / 120 |
| 343514S | 7/16 | 17.0 | 19 | 13 | 63.5 | 84 | 6 / 120 |
| 343516S | 1/2 | 18.2 | 19 | 14 | 63.5 | 113 | 6 / 120 |
| 343518S | 9/16 | 20.7 | 22 | 14 | 65 | 114 | 6 / 120 |
| 343520S | 5/8 | 23.8 | 22 | 16 | 65 | 126 | 6 / 96 |
| 343522S | 11/16 | 24.5 | 22 | 17 | 65 | 138 | 6 / 96 |
| 343524S | 3/4 | 27.0 | 22 | 20 | 65 | 154 | 6 / 96 |
| 343526S | 13/16 | 29.5 | 22 | 22 | 65 | 156 | 6 / 96 |
| 343528S | 7/8 | 30.8 | 22 | 22 | 65 | 172 | 5 / 60 |

Impact Star Socket

3575M

3/8"

- For torx external screw
- DIN 3121



| KT NO. | Size | D1 mm | D2 mm | l mm | L mm | g | kg |
|---------|------|-------|-------|------|------|----|----------|
| 357505M | E5 | 9.6 | 19 | 4.0 | 32 | 31 | 12 / 360 |
| 357506M | E6 | 10.2 | 19 | 5.0 | 32 | 31 | 12 / 360 |
| 357507M | E7 | 10.8 | 19 | 6.0 | 32 | 33 | 12 / 360 |
| 357508M | E8 | 11.5 | 19 | 6.5 | 32 | 35 | 12 / 360 |
| 357510M | E10 | 12.0 | 19 | 7.0 | 32 | 33 | 12 / 360 |
| 357512M | E12 | 14.0 | 19 | 9.0 | 32 | 34 | 12 / 360 |
| 357514M | E14 | 17.0 | 19 | 9.5 | 32 | 40 | 12 / 360 |

Impact Bit Socket

KT No. & D1



- Air pressure must not exceed 90PSI (6.3bar)
- Adjust your air tool to its lowest torque output, should this torque level not be enough, increase it gradually

3051

3/8"

- For phillips head screw
- DIN 3121



| KT NO. | No. | L mm | g | kg |
|--------|-----|------|----|----------|
| 305101 | PH1 | 55 | 33 | 12 / 360 |
| 305102 | PH2 | 55 | 35 | 12 / 360 |
| 305103 | PH3 | 55 | 40 | 12 / 360 |
| 305104 | PH4 | 55 | 45 | 12 / 360 |

3052

3/8"

- For slotted head screw
- DIN 3121



| KT NO. | Tip width mm | L mm | g | kg |
|--------|--------------|------|----|----------|
| 305255 | 5.5 | 55 | 32 | 12 / 360 |
| 305208 | 8 | 55 | 39 | 12 / 360 |
| 305210 | 10 | 55 | 45 | 12 / 360 |

3055M

3/8"

- For hexagon head screw
- DIN 3121



| KT NO. | mm | L mm | Max. torq N-m | g | kg |
|---------|-----|------|---------------|----|----------|
| 305504M | H4 | 55 | 20.8 | 34 | 12 / 360 |
| 305505M | H5 | 55 | 36.0 | 38 | 12 / 360 |
| 305506M | H6 | 55 | 62.4 | 40 | 12 / 360 |
| 305507M | H7 | 55 | 97.0 | 43 | 12 / 360 |
| 305508M | H8 | 55 | 144.0 | 46 | 12 / 360 |
| 305510M | H10 | 55 | 264.0 | 55 | 12 / 360 |
| 305512M | H12 | 55 | 480.0 | 65 | 12 / 360 |
| 305514M | H14 | 55 | 650.0 | 77 | 12 / 288 |
| 305516M | H16 | 55 | 680.0 | 91 | 12 / 288 |
| 305517M | H17 | 55 | 715.0 | 99 | 12 / 288 |

3055S

3/8"

- For hexagon head
- DIN 3121



| KT NO. | inch | L mm | Max. torq N-m | g | kg |
|---------|------|------|---------------|----|----------|
| 305504S | 1/8 | 55 | 18.8 | 34 | 12 / 360 |
| 305545S | 9/64 | 55 | 20.8 | 34 | 12 / 360 |
| 305505S | 5/32 | 55 | 22.5 | 36 | 12 / 360 |
| 305506S | 3/16 | 55 | 36.0 | 36 | 12 / 360 |
| 305507S | 7/32 | 55 | 62.4 | 38 | 12 / 360 |
| 305508S | 1/4 | 55 | 93.6 | 41 | 12 / 360 |
| 305510S | 5/16 | 55 | 144.0 | 46 | 12 / 360 |
| 305512S | 3/8 | 55 | 264.0 | 54 | 12 / 360 |
| 305516S | 1/2 | 55 | 518.0 | 71 | 12 / 360 |