


# Impact Wrench

## 33421


- Nickel chrome molybdenum square drive
- Variable speed trigger
- Muffled on front exhaust



33421

KT NO.	Square drive inch mm	Type Std./Long anvil	Std. bolt size inch mm	Free speed R.P.M.	Max. torque ft-lb N-m	Overall length inch mm	Air inlet inch	Air hose ID	Air pressure bar psi	Avg. air consumption L/min CFM	Sound DBA	Vib M/S <sup>2</sup>	Net weight kgs lbs
33421-040	1/2" 12.70	Std. anvil	5/8" M16	8000	500 678	6-3/4" 171	1/4" BSPT	3/8"	6.2 90	113 4.0	101.02	8.70	2.56 5.64 1 / 8
33421-041	1/2" 12.70	Std. anvil	5/8" M16	8000	500 678	6-3/4" 171	1/4" NPT	3/8"	6.2 90	113 4.0	101.02	8.70	2.56 5.64 1 / 8

## 33411-040



33411-040

## 33411-050 / 33412-050



33411-050



33412-050

KT NO.	Square drive inch mm	Type Std./Long anvil	Std. bolt size inch mm	Free speed R.P.M.	Max. torque ft-lb N-m	Overall length inch mm	Air inlet inch	Air hose ID	Air pressure bar psi	Avg. air consumption L/min CFM	Sound DBA	Vib M/S <sup>2</sup>	Net weight kgs lbs
33411-040	1/2" 12.70	Std. anvil	5/8" M16	8000	500 678	7-23/64" 187	1/4" BSPT	3/8"	6.2 90	113 4.0	95.22	4.85	2.60 5.73 1 / 8
33411-041	1/2" 12.70	Std. anvil	5/8" M16	8000	500 678	7-23/64" 187	1/4" NPT	3/8"	6.2 90	113 4.0	95.22	4.85	2.60 5.73 1 / 8
33411-050	1/2" 12.70	Std. anvil	3/4" M19	8000	650 881	7-41/64" 194	1/4" BSPT	3/8"	6.2 90	125 4.4	96.50	8.13	2.80 6.17 1 / 8
33411-051	1/2" 12.70	Std. anvil	3/4" M19	8000	650 881	7-41/64" 194	1/4" NPT	3/8"	6.2 90	125 4.4	96.50	8.13	2.80 6.17 1 / 8
33412-050	1/2" 12.70	Long anvil	3/4" M19	8000	650 881	9-23/64" 238	1/4" BSPT	3/8"	6.2 90	125 4.4	96.19	6.84	3.20 7.05 1 / 8
33412-051	1/2" 12.70	Long anvil	3/4" M19	8000	650 881	9-23/64" 238	1/4" NPT	3/8"	6.2 90	125 4.4	96.19	6.84	3.20 7.05 1 / 8