

UNIVERSAL

Camshaft Sprocket Puller

9AT3-A04

- Use to hold and remove the camshaft sprocket without damaging the sprocket
- Use with 3/8" square drive tool or 19mm wrench
- Suitable for most sprockets from Ø60 to Ø100 mm



| KT NO. | Capacity mm |  |  |
|----------|-------------|---|---|
| 9AT3-A04 | 60~100 | 1437 | 1 / 12 |


UNIVERSAL

Belt Tensioner Lock Pin Set

9AT3-B01

- Designed for retaining tensioner plunger in fixed position while replacing timing belt
- Suitable for common vehicle and engine

 17  20 / 100



- CONTENTS :
- 0.79mm / .0310"
 - 1.21mm / .0476"
 - 1.41mm / .0560"
 - 1.51mm / .0594"
 - 1.71mm / .0670"
 - 1.92mm / .0760"


UNIVERSAL

Dial Test Indicator

9AT3-F01

- Use to measure and accurately find the piston TDC position
- This tool has to use with TDC Indicator 9AT3-F02
- It can be used for mechanical circularity, flatness.....etc

 63  1 / 100



UNIVERSAL

TDC Indicator

9AT3-F02

- Use to measure if the cylinder piston is at TDC position
- This tool has to use with Dial Test Indicator 9AT3-F01

 292  1 / 30

